

Description

IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. RFC™ Reflection Free Contour main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control. Remote EC electronic converter, IP66.

TM-C 80 poles. Tubular steel, constant section, hot dipped galvanised. Powdercoat finish to match luminaire. Surface mounting flange plate. Service door including PCS hardware.

Attention: This product is suitable for operation in exterior tennis court installations only.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9016 Traffic white	RAL7016 Anthracite grey	RAL9007 Grey aluminium
Ingress protection	IP66			
Impact resistance	IK08			

Electrical description

Driver / Ballast	Integral EC electronic converter
Energy efficiency	This product is suitable for operation in exterior tennis court installations only.

Additional information

Windage	0.046
Lifetime	TM-C 80 poles. Tubular steel, constant section, hot dipped galvanised. Powdercoat finish to match luminaire. Surface mounting flange plate. Service door including PCS hardware.


Options

Light distribution



[A60] asymmetric, forward throw

Colour temperature




4000K

Nominal Watt

207 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	108-9075	LED-48/207W/4000K	22749 lm	207 W	80

[A60] asymmetric, forward throw