

Description

IP67, Class I. IK09. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. PMMA. Linear PMMA LED lens. 1.2 m connecting cable, UV stabilized, PVC free. Luminaire is factory sealed and does not need to be opened during installation and can be tilted up to 180°. Integral LED driver with DALI interface.

Separate LED driver on request.

Specifications

Material description

| | | | | | | | | | | | | | | | | | |
|----------------------|--|----------------|-----------------|----------------|----------------|--------------|-----------------|---------------|-----------------|----------------|--|--|--|----------------|--|--|--|
| Body | Marine-grade, all-aluminium construction | | | | | | | | | | | | | | | | |
| Lens | PMMA | | | | | | | | | | | | | | | | |
| Colours | <table><tr><td>RAL9004</td><td>RAL9006</td><td>RAL9016</td><td>RAL7016</td></tr><tr><td>Signal black</td><td>White aluminium</td><td>Traffic white</td><td>Anthracite grey</td></tr><tr><td>RAL9007</td><td></td><td></td><td></td></tr><tr><td>Grey aluminium</td><td></td><td></td><td></td></tr></table> | RAL9004 | RAL9006 | RAL9016 | RAL7016 | Signal black | White aluminium | Traffic white | Anthracite grey | RAL9007 | | | | Grey aluminium | | | |
| RAL9004 | RAL9006 | RAL9016 | RAL7016 | | | | | | | | | | | | | | |
| Signal black | White aluminium | Traffic white | Anthracite grey | | | | | | | | | | | | | | |
| RAL9007 | | | | | | | | | | | | | | | | | |
| Grey aluminium | | | | | | | | | | | | | | | | | |
| Gasket | Silicone rubber gasket | | | | | | | | | | | | | | | | |
| Fasteners | PCS Polymer Coated Stainless Steel Hardware | | | | | | | | | | | | | | | | |
| Ingress protection | IP67 | | | | | | | | | | | | | | | | |
| Impact resistance | IK09 | | | | | | | | | | | | | | | | |
| Corrosion resistance | 5CE | | | | | | | | | | | | | | | | |

Electrical description

| | |
|-------------------|---|
| Power supply | 220-240V / 50-60 Hz |
| Driver / Ballast | Integral LED driver with DALI Interface |
| Energy efficiency | D (Light source) |

Additional information

| | |
|----------|------------------------|
| Lifetime | Ta=25° L90B10 > 90000h |
|----------|------------------------|

Options

Light distribution



[LA10] asymmetric linear, wallwash

Colour temperature



3000K



4000K




2700K

Nominal Watt

20 W

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|---|----------|------------------|--------------|-------------------|-----|
|  | 187-0549 | LED-32/20W/2700K | 2049.8 lm | 20 W | 80 |
| | 187-0014 | LED-32/20W/3000K | 2049.8 lm | 20 W | 80 |
| | 187-0329 | LED-32/20W/4000K | 2049.8 lm | 20 W | 80 |

[LA10] asymmetric linear, wallwash