

Description

IP67, Class I. IK09. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. PMMA cover. Silicone rubber gasket. Linear PMMA LED lens. 1.2 m connecting cable, UV stabilized, PVC free. Luminaire is factory sealed and does not need to be opened during installation and can be tilted up to 180°. Integral LED driver with DALI interface.

Separate LED driver on request.

Specifications

Material description

| | | | |
|----------------------|---|-----------------------------------|----------------------------------|
| Body | Marine-grade, all-aluminium construction | | |
| Lens | PMMA | | |
| Colours | RAL9004 Signal black | RAL9006 White aluminium | RAL9007 Grey aluminium |
| Gasket | Silicone rubber gasket | | |
| Fasteners | PCS Polymer Coated Stainless Steel Hardware (unpainted) | | |
| Ingress protection | IP67 | | |
| Impact resistance | IK09 | | |
| Corrosion resistance | 5CE+Primer | | |

Electrical description

| | |
|-------------------|--|
| Power supply | 230V / 50 Hz |
| Driver / Ballast | Integral LED driver with DALI Interface |
| Energy efficiency | The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. |

Additional information

| | |
|----------|------------------------|
| Lifetime | Ta=40° L90B10 > 90000h |
|----------|------------------------|

Options

Light distribution



[LA10] asymmetric linear, wallwash

Colour temperature



3000K



4000K




2700K

Nominal Watt

20 W

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI |
|---|----------|------------------|--------------|-------------------|-----|
|  | 187-0549 | LED-32/20W/2700K | 2049.8 lm | 20 W | 80 |
| | 187-0014 | LED-32/20W/3000K | 2049.8 lm | 20 W | 80 |
| | 187-0329 | LED-32/20W/4000K | 2049.8 lm | 20 W | 80 |

[LA10] asymmetric linear, wallwash