

Description

IP67. Class I. IK09. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Linear PMMA LED lens, PMMA cover. 4 ft connecting cable, UV stabilized, PVC free. Integral LED driver; separate LED driver available instead, on request at time of order. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation and can be tilted up to 180°.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade, all-aluminium construction			
Lens	PMMA			
Colors	RAL9004 Signal black	RAL9016 Traffic white	RAL8019 Grey brown	RAL9007 Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP67			
Impact resistance	IK09			
Corrosion resistance	5CE			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral LED driver with DALI Interface
Energy efficiency	D (Light source)

Additional information

Length x Width (inches)	24.72 x 1.65
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations. Meets ANSI C136.31 - 3G Vibration Rating for Bridge and Overpass Applications.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution **Color temperature** **Nominal Watt**



[LA10]



3000K




4000K



2700K

20 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	187-0549	LED-32/20W/2700K	2049.8 lm	20 W	80
	187-0014	LED-32/20W/3000K	2049.8 lm	20 W	80
	187-0329	LED-32/20W/4000K	2049.8 lm	20 W	80

[LA10]