

### Description

IP67, Class I. IK09. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. PMMA cover. Silicone rubber gasket. Linear PMMA LED lens. 1.2 m connecting cable, UV stabilized, PVC free. Luminaire is factory sealed and does not need to be opened during installation and can be tilted up to 180°. Integral LED driver with DALI interface. Optional 2200 K version available. To be specified at time of ordering.

Separate LED driver on request.

## Specifications

### Material description

Body	Marine-grade, all-aluminium construction		
Lens	PMMA		
Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>
	Signal black	White aluminium	Grey aluminium
Gasket	Silicone rubber gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)		
Ingress protection	IP67		
Impact resistance	IK09		
Corrosion resistance	5CE+Primer		








### Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral LED driver with DALI Interface
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.




### Additional information

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

**Options****Light distribution**

	[LM] symmetric linear, medium beam
	[LE] symmetric linear, narrow beam
	[LEE] symmetric linear, very narrow beam
	[LB] symmetric linear, wide beam
	[LB/IW] symmetric linear, wide beam
	[LM/IW] symmetric linear, medium beam
	[LE/IW] symmetric linear, narrow beam








**Colour temperature**

	3000K
	4000K
	2700K

**Nominal Watt**

20 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	187-0534	LED-32/20W/2700K	1915.7 lm	20 W	80
	187-0024	LED-32/20W/3000K	1915.7 lm	20 W	80
	187-0038	LED-32/20W/4000K	1915.7 lm	20 W	80
[LB] symmetric linear, wide beam					
	187-0581	LED-32/20W/2700K	851.5 lm	20 W	80
	187-0486	LED-32/20W/3000K	851.5 lm	20 W	80
	187-0487	LED-32/20W/4000K	851.5 lm	20 W	80
[LB/IW] symmetric linear, wide beam					
	187-0535	LED-32/20W/2700K	2101.3 lm	20 W	80
	187-0006	LED-32/20W/3000K	2101.3 lm	20 W	80
	187-0036	LED-32/20W/4000K	2101.3 lm	20 W	80
[LE] symmetric linear, narrow beam					
	187-0583	LED-32/20W/2700K	1113.7 lm	20 W	80
	187-0490	LED-32/20W/3000K	1113.7 lm	20 W	80
	187-0491	LED-32/20W/4000K	1113.7 lm	20 W	80
[LE/IW] symmetric linear, narrow beam					
	187-0536	LED-32/20W/2700K	2405.9 lm	20 W	80
	187-0010	LED-32/20W/3000K	2405.9 lm	20 W	80
	187-0037	LED-32/20W/4000K	2405.9 lm	20 W	80
[LEE] symmetric linear, very narrow beam					
	187-0460	LED-32/20W/2700K	2140.4 lm	20 W	80
	187-0002	LED-32/20W/3000K	2140.4 lm	20 W	80
	187-0035	LED-32/20W/4000K	2140.4 lm	20 W	80
[LM] symmetric linear, medium beam					
	187-0582	LED-32/20W/2700K	1068.8 lm	20 W	80
	187-0488	LED-32/20W/3000K	1068.8 lm	20 W	80
	187-0489	LED-32/20W/4000K	1068.8 lm	20 W	80
[LM/IW] symmetric linear, medium beam					