

### Description

IP67, Class I. IK09. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. PMMA. Linear PMMA LED lens. 1.2 m connecting cable, UV stabilized, PVC free. Luminaire is factory sealed and does not need to be opened during installation and can be tilted up to 180°. Integral LED driver with DALI interface.

Separate LED driver on request.

## Specifications

### Material description

Body	Marine-grade, all-aluminium construction								
Lens	PMMA								
Colours	<table><tr><td><b>RAL9004</b> Signal black</td><td><b>RAL9006</b> White aluminium</td><td><b>RAL9016</b> Traffic white</td><td><b>RAL7016</b> Anthracite grey</td></tr><tr><td><b>RAL9007</b> Grey aluminium</td><td></td><td></td><td></td></tr></table>	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey	<b>RAL9007</b> Grey aluminium			
<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey						
<b>RAL9007</b> Grey aluminium									
Gasket	Silicone rubber gasket								
Fasteners	PCS Polymer Coated Stainless Steel Hardware								
Ingress protection	IP67								
Impact resistance	IK09								
Corrosion resistance	5CE								

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral LED driver with DALI Interface
Energy efficiency	D (Light source)

### Additional information

Lifetime	Ta=25° L90B10 > 90000h
----------	------------------------

**Options**

**Light distribution**



[LA10] asymmetric linear, wallwash

**Colour temperature**



3000K



4000K




2700K

**Nominal Watt**

30 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	187-0550	LED-48/30W/2700K	3074.8 lm	30 W	80
	187-0015	LED-48/30W/3000K	3074.8 lm	30 W	80
	187-0330	LED-48/30W/4000K	3074.8 lm	30 W	80

[LA10] asymmetric linear, wallwash