




Description

IP67, Class I. IK09. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. PMMA cover. Silicone rubber gasket. Linear PMMA LED lens. 1.2 m connecting cable, UV stabilized, PVC free. Luminaire is factory sealed and does not need to be opened during installation and can be tilted up to 180°. Integral LED driver with DALI interface.

Separate LED driver on request.

Specifications

Material description

Body	Marine-grade, all-aluminium construction		
Lens	PMMA		
Colours			
	Signal black	White aluminium	Grey aluminium
Gasket	Silicone rubber gasket		
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)		
Ingress protection	IP67		
Impact resistance	IK09		
Corrosion resistance	5CE+Primer		

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral LED driver with DALI Interface
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Additional information

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

Options

Light distribution **Colour temperature** **Nominal Watt**



[LA10]



3000K




4000K



2700K

30 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	187-0550	LED-48/30W/2700K	3074.8 lm	30 W	80
	187-0015	LED-48/30W/3000K	3074.8 lm	30 W	80
	187-0330	LED-48/30W/4000K	3074.8 lm	30 W	80

[LA10]