

**Description**

IP67. Class I. IK09. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Linear PMMA LED lens, PMMA cover. 4 ft connecting cable, UV stabilized, PVC free. Integral LED driver; separate LED driver available instead, on request at time of order. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation and can be tilted up to 180°.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.  
 Example: XXX-XXXX-9004 (Black)  
 + XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Marine-grade, all-aluminium construction			
Lens	PMMA			
Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown	<b>RAL9007</b> Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP67			
Impact resistance	IK09			
Corrosion resistance	5CE			

### Electrical description


Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral LED driver with DALI Interface
Energy efficiency	D (Light source)

### Additional information

Length x Width (inches)	48.35 x 1.65
Listings	Please contact WE-EF for UL/ETL listing status.
Lifetime	Ta=25°/40° L90B10 > 90000h


**Options**

**Light distribution**    **Color temperature**    **Nominal Watt**



40 W

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	187-0237	LED-64/40W/2700K	4099.7 lm	40 W	80
	187-0016	LED-64/40W/3000K	4099.7 lm	40 W	80
	187-0331	LED-64/40W/4000K	4099.7 lm	40 W	80

[LA10]