

Description

IP67. Class I. IK09. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Linear PMMA LED lens, PMMA cover. 4 ft connecting cable, UV stabilized, PVC free. Integral LED driver; separate LED driver available instead, on request at time of order. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation and can be tilted up to 180°.

Specify product with 7 Digit product code - Finish Color.
 Accessories, such as mounting, optical, and electrical, must be specified separately.
 Example: XXX-XXXX-9004 (Black)
 + XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade, all-aluminium construction			
Lens	PMMA			
Colors	RAL9004	RAL9016	RAL8019	RAL9007
	Signal black	Traffic white	Grey brown	Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP67			
Impact resistance	IK09			
Corrosion resistance	5CE			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	LED driver with 0-10V Interface
Energy efficiency	D (Light source)

Additional information

Listings	ETL Listed. Suitable for wet locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

Options

Light distribution

Color temperature

Nominal Watt



[LM] symmetric linear, medium beam



3000K

40 W



[LN] symmetric linear, narrow beam



4000K



[LW] symmetric linear, wide beam



2700K



[LVN] symmetric linear, very narrow beam



[LB] symmetric linear, wide beam



[LE] symmetric linear, narrow beam



[LEE] symmetric linear, very narrow beam



[LB/IW] symmetric linear, wide beam



[LW/IW] symmetric linear, wide beam



[LM/IW] symmetric linear, medium beam









[LE/IW] symmetric linear, narrow beam



[LN/IW] symmetric linear, narrow beam

Configurations







Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	187-0541	LED-64/40W/2700K	3831.5 lm	40 W	80
[LB] symmetric linear, wide beam					
	187-0591	LED-64/40W/2700K	1703 lm	40 W	80
[LB/IW] symmetric linear, wide beam					
	187-0543	LED-64/40W/2700K	4202.5 lm	40 W	80
[LE] symmetric linear, narrow beam					
	187-0593	LED-64/40W/2700K	2227.4 lm	40 W	80
[LE/IW] symmetric linear, narrow beam					
	187-0544	LED-64/40W/2700K	4811.9 lm	40 W	80
[LEE] symmetric linear, very narrow beam					
	187-0542	LED-64/40W/2700K	4280.8 lm	40 W	80
	187-0004_us	LED-64/40W/3000K	4280.8 lm	40 W	80
	187-0043_us	LED-64/40W/4000K	4280.8 lm	40 W	80
[LM] symmetric linear, medium beam					
	187-0592	LED-64/40W/2700K	2137.6 lm	40 W	80
	187-0508_us	LED-64/40W/3000K	2137.6 lm	40 W	80

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 05/03/2026

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	187-0509_us	LED-64/40W/4000K	2137.6 lm	40 W	80
[LM/IW] symmetric linear, medium beam					
	187-0008_us	LED-64/40W/3000K	4202.5 lm	40 W	80
	187-0044_us	LED-64/40W/4000K	4202.5 lm	40 W	80
[LN] symmetric linear, narrow beam					
	187-0510_us	LED-64/40W/3000K	2227.4 lm	40 W	80
	187-0511_us	LED-64/40W/4000K	2227.4 lm	40 W	80
[LN/IW] symmetric linear, narrow beam					
	187-0012_us	LED-64/40W/3000K	4811.9 lm	40 W	80
	187-0045_us	LED-64/40W/4000K	4811.9 lm	40 W	80
[LVN] symmetric linear, very narrow beam					
	187-0026_us	LED-64/40W/3000K	3831.5 lm	40 W	80
	187-0046_us	LED-64/40W/4000K	3831.5 lm	40 W	80
[LW] symmetric linear, wide beam					
	187-0506_us	LED-64/40W/3000K	1703 lm	40 W	80
	187-0507_us	LED-64/40W/4000K	1703 lm	40 W	80
[LW/IW] symmetric linear, wide beam					