

Description

IP67, Class I. IK09. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. PMMA cover. Silicone rubber gasket. Linear PMMA LED lens. 1.2 m connecting cable, UV stabilized, PVC free. Luminaire is factory sealed and does not need to be opened during installation and can be tilted up to 180°. Integral LED driver with DALI interface.

Separate LED driver on request.

Specifications

Material description

Body	Marine-grade, all-aluminium construction						
Lens	PMMA						
Colours	<table><tr><td>RAL9004</td><td>RAL9006</td><td>RAL9007</td></tr><tr><td>Signal black</td><td>White aluminium</td><td>Grey aluminium</td></tr></table>	RAL9004	RAL9006	RAL9007	Signal black	White aluminium	Grey aluminium
RAL9004	RAL9006	RAL9007					
Signal black	White aluminium	Grey aluminium					
Gasket	Silicone rubber gasket						
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)						
Ingress protection	IP67						
Impact resistance	IK09						
Corrosion resistance	5CE+Primer						











Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral LED driver with DALI Interface
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.








Additional information

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

Options

Light distribution	Colour temperature	Nominal Watt
 [LM]	 3000K	40 W
 [LE]	 4000K	
 [LB]	 2700K	
 [LEE]		
 [LB/IW]		
 [LM/IW]		
 [LE/IW]		

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	187-0541	LED-64/40W/2700K	3831.5 lm	40 W	80
	187-0026	LED-64/40W/3000K	3831.5 lm	40 W	80
	187-0046	LED-64/40W/4000K	3831.5 lm	40 W	80
[LB]					
	187-0591	LED-64/40W/2700K	1703 lm	40 W	80
	187-0506	LED-64/40W/3000K	1703 lm	40 W	80
	187-0507	LED-64/40W/4000K	1703 lm	40 W	80
[LB/IW]					
	187-0543	LED-64/40W/2700K	4202.5 lm	40 W	80
	187-0008	LED-64/40W/3000K	4202.5 lm	40 W	80
	187-0044	LED-64/40W/4000K	4202.5 lm	40 W	80
[LE]					
	187-0593	LED-64/40W/2700K	2227.4 lm	40 W	80
	187-0510	LED-64/40W/3000K	2227.4 lm	40 W	80
	187-0511	LED-64/40W/4000K	2227.4 lm	40 W	80
[LE/IW]					
	187-0544	LED-64/40W/2700K	4811.9 lm	40 W	80
	187-0012	LED-64/40W/3000K	4811.9 lm	40 W	80
	187-0045	LED-64/40W/4000K	4811.9 lm	40 W	80
[LEE]					
	187-0542	LED-64/40W/2700K	4280.8 lm	40 W	80
	187-0004	LED-64/40W/3000K	4280.8 lm	40 W	80
	187-0043	LED-64/40W/4000K	4280.8 lm	40 W	80
[LM]					
	187-0592	LED-64/40W/2700K	2137.6 lm	40 W	80
	187-0508	LED-64/40W/3000K	2137.6 lm	40 W	80
	187-0509	LED-64/40W/4000K	2137.6 lm	40 W	80
[LM/IW]					