

**Description**

IP67. Class I. IK09. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Linear PMMA LED lens, PMMA cover. 4 ft connecting cable, UV stabilized, PVC free. Integral LED driver; separate LED driver available instead, on request at time of order. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation and can be tilted up to 180°.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.  
 Example: XXX-XXXX-9004 (Black)  
 + XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Marine-grade, all-aluminium construction			
Lens	PMMA			
Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown	<b>RAL9007</b> Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP67			
Impact resistance	IK09			
Corrosion resistance	5CE			











### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	LED driver with 0-10V Interface
Energy efficiency	D (Light source)








### Additional information

Length x Width (inches)	48.35 x 1.65
Listings	ETL Listed. Suitable for wet locations.
Lifetime	Ta=25°/40° L90B10 > 90000h

**Options**

Light distribution	Color temperature	Nominal Watt
 [LM]	 3000K	40 W
 [LE]	 4000K	
 [LB]	 2700K	
 [LEE]		
 [LB/IW]		
 [LM/IW]		
 [LE/IW]		

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
	187-0541	LED-64/40W/2700K	3831.5 lm	40 W	80
	187-0026	LED-64/40W/3000K	3831.5 lm	40 W	80
	187-0046	LED-64/40W/4000K	3831.5 lm	40 W	80
[LB]					
	187-0591	LED-64/40W/2700K	1703 lm	40 W	80
	187-0506	LED-64/40W/3000K	1703 lm	40 W	80
	187-0507	LED-64/40W/4000K	1703 lm	40 W	80
[LB/IW]					
	187-0543	LED-64/40W/2700K	4202.5 lm	40 W	80
	187-0008	LED-64/40W/3000K	4202.5 lm	40 W	80
	187-0044	LED-64/40W/4000K	4202.5 lm	40 W	80
[LE]					
	187-0593	LED-64/40W/2700K	2227.4 lm	40 W	80
	187-0510	LED-64/40W/3000K	2227.4 lm	40 W	80
	187-0511	LED-64/40W/4000K	2227.4 lm	40 W	80
[LE/IW]					
	187-0544	LED-64/40W/2700K	4811.9 lm	40 W	80
	187-0012	LED-64/40W/3000K	4811.9 lm	40 W	80
	187-0045	LED-64/40W/4000K	4811.9 lm	40 W	80
[LEE]					
	187-0542	LED-64/40W/2700K	4280.8 lm	40 W	80
	187-0004	LED-64/40W/3000K	4280.8 lm	40 W	80
	187-0043	LED-64/40W/4000K	4280.8 lm	40 W	80
[LM]					
	187-0592	LED-64/40W/2700K	2137.6 lm	40 W	80
	187-0508	LED-64/40W/3000K	2137.6 lm	40 W	80
	187-0509	LED-64/40W/4000K	2137.6 lm	40 W	80
[LM/IW]					