




**Description**

IP55, Class I. IK10. Marine-grade, all-aluminium construction. 5CE superior corrosion protection including PCS hardware. Polycarbonate prismatic lens. Silicone rubber gaskets.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output.



## Specifications

### Material description

Body	Marine-grade, all-aluminium construction			
Lens	Polycarbonate lens			
Colours	<b>RAL9004</b>	<b>RAL9016</b>	<b>RAL7016</b>	<b>RAL9007</b>
	Signal black	Traffic white	Anthracite grey	Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP55			
Impact resistance	IK10			
Corrosion resistance	5CE			



### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment
Surge protection	6/6 kV (optional SP10)

### Additional information

Lifetime	Ta=25° L80B10 > 54000h
----------	------------------------

**Options**

Light distribution	Colour temperature	Nominal Watt
□	 3000K	8 W
	 4000K	

### Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
[]	115-9687	LED-2/8W/3000K	263.1 lm	8 W	85
	115-9688	LED-2/8W/4000K	282.4 lm	8 W	85