**Description**

IP55. Class I. IK10. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. CAD-optimized indirect optics for superior illumination and glare control. 0-10V Dimming comes standard with luminaire.

Recommended mounting height 10-20 ft.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Marine-grade, die-cast aluminium alloy			
Lens	Clear polycarbonate outer lens			
Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown	<b>RAL9007</b> Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel hardware			
Ingress protection	IP55			
Impact resistance	IK10			
Corrosion resistance	5CE			

### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter
Surge protection	In-line bracket 10kV Surge Protector
Energy efficiency	D (Light source)

### Additional information

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Windage	0.11 m <sup>2</sup>
Lifetime	Ta=25°/40° L70B50 > 50000h

**Options**

**Light distribution**

[]



[C60] symmetric distribution

**Color temperature**



2700K


**Nominal Watt**

0 W

17 W

24 W

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
[]	159-0298_us		1863.3 lm	0 W	80
	159-0299_us		1942.2 lm	0 W	80
	159-0306_us		2385.2 lm	0 W	80
	159-0307_us		2488.4 lm	0 W	80
	159-0334	LED-1/17W/2700K	1781.3 lm	17 W	80
	159-0335	LED-1/24W/2700K	2458.1 lm	24 W	80

[C60] symmetric distribution