**Description**

IP55. Class I. IK10. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gaskets. Polycarbonate main lens. CAD-optimized indirect optics for superior illumination and glare control. 0-10V Dimming comes standard with luminaire.

Recommended mounting height 15-30 ft.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Clear polycarbonate outer lens			
Colors	<b>RAL9004</b> Signal black	<b>RAL9016</b> Traffic white	<b>RAL8019</b> Grey brown	<b>RAL9007</b> Grey aluminium
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel hardware			
Ingress protection	IP55			
Impact resistance	IK10			
Corrosion resistance	5CE			

### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter
Surge protection	In-line bracket 10kV Surge Protector
Energy efficiency	D-E (Light source)

### Additional information




Height x Diameter (inches)	21.65 x 22.83
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Windage	1.58 ft <sup>2</sup>
Lifetime	Ta=25°/40° L70B50 > 50000h

**Options**

**Light distribution**    **Color temperature**    **Nominal Watt**




[C60]

	3000K
	4000K
	2700K

17 W  
24 W

### Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 [C60]	159-0336	LED-1/17W/2700K	1781.3 lm	17 W	80
	159-0302	LED-1/17W/3000K	1863.3 lm	17 W	80
	159-0303	LED-1/17W/4000K	1942.2 lm	17 W	80
	159-0337	LED-1/24W/2700K	2458.1 lm	24 W	80
	159-0308	LED-1/24W/3000K	2561.2 lm	24 W	80
	159-0309	LED-1/24W/4000K	2670.5 lm	24 W	80