



Description

IP55, Class I. Class II on request. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. Polycarbonate main lens. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Recommended mounting height 3,0-4,5 m

Specifications

Material description

Colours	RAL9004	RAL9006	RAL9007	RAL7016
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	RAL9016			
	Traffic white			
	Ingress protection	IP55		
Impact resistance	IK10			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Energy efficiency	C-D (Light source)

Additional information

Windage	0.147 m ²
Lifetime	Ta=25° L70B50 > 90000h

Options

Light distribution



[R65] rectangular, side throw



[S65] asymmetric, side throw

Colour temperature



2200K



2700K



3000K





4000K

Nominal Watt

13 W

18 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [R65] rectangular, side throw	159-0355	LED-9/13W/2200K	1488.7 lm	13 W	70
	159-0354	LED-9/13W/2700K	1488.7 lm	13 W	80
	159-0353	LED-9/13W/3000K	1600.3 lm	13 W	80
	159-0352	LED-9/13W/4000K	1712 lm	13 W	80
	159-0346	LED-9/18W/2200K	2009.7 lm	18 W	70
	159-0345	LED-9/18W/2700K	2009.7 lm	18 W	80
	159-0342	LED-9/18W/3000K	2158.6 lm	18 W	80
	159-0347	LED-9/18W/4000K	2307.4 lm	18 W	80
 [S65] asymmetric, side throw	159-0359	LED-9/13W/2200K	1386.6 lm	13 W	70
	159-0358	LED-9/13W/2700K	1386.6 lm	13 W	80
	159-0357	LED-9/13W/3000K	1490.6 lm	13 W	80
	159-0356	LED-9/13W/4000K	1594.6 lm	13 W	80
	159-0351	LED-9/18W/2200K	1872 lm	18 W	70
	159-0350	LED-9/18W/2700K	1872 lm	18 W	80
	159-0349	LED-9/18W/3000K	2010.6 lm	18 W	80
	159-0348	LED-9/18W/4000K	2149.3 lm	18 W	80