

Description

IP66, Class I. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. PMMA main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral electronic converter with DALI interface in thermally separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Optional 2200 K version available. To be specified at time of ordering.

Including 0.5 m cable with a cable connector.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP66			
Impact resistance	IK09			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral electronic converter with DALI interface in thermally separated compartment
Surge protection	6/6 kV (optional SP10)
Energy efficiency	C-D (Light source)

Additional information

Windage	0.130 m ²
Lifetime	Ta=25° L90B10 > 90000h

Options

Light distribution



[R65] rectangular, side throw



[S65] asymmetric, side throw

Colour temperature



2700K



3000K



4000K



Nominal Watt

9 W

18 W

27 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [R65] rectangular, side throw	115-1670	LED-9/9W/2700K	999.2 lm	9 W	80
	115-1671	LED-9/9W/3000K	1068.1 lm	9 W	80
	115-1672	LED-9/9W/4000K	1171.5 lm	9 W	80
	115-1673	LED-9/18W/2700K	1860.6 lm	18 W	80
	115-1674	LED-9/18W/3000K	1998.5 lm	18 W	80
	115-1675	LED-9/18W/4000K	2136.3 lm	18 W	80
	115-1676	LED-9/27W/2700K	2825.4 lm	27 W	80
	115-1677	LED-9/27W/3000K	2963.2 lm	27 W	80
	115-1678	LED-9/27W/4000K	3101 lm	27 W	80
 [S65] asymmetric, side throw	115-1679	LED-9/9W/2700K	968.9 lm	9 W	80
	115-1680	LED-9/9W/3000K	1035.7 lm	9 W	80
	115-1681	LED-9/9W/4000K	1136 lm	9 W	80
	115-1682	LED-9/18W/2700K	1804.2 lm	18 W	80
	115-1683	LED-9/18W/3000K	1937.8 lm	18 W	80
	115-1684	LED-9/18W/4000K	2071.5 lm	18 W	80
	115-1685	LED-9/27W/2700K	2739.7 lm	27 W	80
	115-1686	LED-9/27W/3000K	2873.3 lm	27 W	80
	115-1687	LED-9/27W/4000K	3007 lm	27 W	80