

Description

IP66, Class I. Class II on request. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. PMMA main lens. Integral EC electronic converter in thermally separated compartment. DALI. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Optional 2200 K version available. To be specified at time of ordering.

Specifications

Material description

Colours	RAL9004	RAL9006	RAL9007	RAL7016
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	RAL9016			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK09			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter. DALI
Surge protection	6/6 kV (optional SP10)
Energy efficiency	C-D (Light source)

Additional information

Windage	0.160 m ²
Lifetime	Ta=25° L90B10 > 90000h

Options

Light distribution



[R65] rectangular, side throw



[S65] asymmetric, side throw

Colour temperature



2700K



3000K



4000K



Nominal Watt

9 W

18 W

27 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	
 <p>[R65] rectangular, side throw</p>	115-1712	LED-9/9W/2700K	1024.5 lm	9 W	80	
	115-1712-70	LED-9/9W/2700K	1095.2 lm	9 W	70	
	115-1713	LED-9/9W/3000K	1095.2 lm	9 W	80	
	115-1713-70	LED-9/9W/3000K	1271.8 lm	9 W	70	
	115-1714	LED-9/9W/4000K	1201.2 lm	9 W	80	
	115-1714-70	LED-9/9W/4000K	1342.5 lm	9 W	70	
	115-1715	LED-9/18W/2700K	1907.7 lm	18 W	80	
	115-1715-70	LED-9/18W/2700K	2049 lm	18 W	70	
	115-1716	LED-9/18W/3000K	2049 lm	18 W	80	
	115-1716-70	LED-9/18W/3000K	2331.7 lm	18 W	70	
	115-1717	LED-9/18W/4000K	2190.4 lm	18 W	80	
	115-1717-70	LED-9/18W/4000K	2473 lm	18 W	70	
	115-1718	LED-9/27W/2700K	2896.9 lm	27 W	80	
	115-1718-70	LED-9/27W/2700K	3320.9 lm	27 W	70	
	115-1719	LED-9/27W/3000K	3038.2 lm	27 W	80	
	115-1719-70	LED-9/27W/3000K	3462.2 lm	27 W	70	
	115-1720	LED-9/27W/4000K	3179.6 lm	27 W	80	
	115-1720-70	LED-9/27W/4000K	3603.5 lm	27 W	70	
	 <p>[S65] asymmetric, side throw</p>	115-1721	LED-9/9W/2700K	1000.3 lm	9 W	80
		115-1721-70	LED-9/9W/2700K	1069.3 lm	9 W	70
115-1722		LED-9/9W/3000K	1069.3 lm	9 W	80	
115-1722-70		LED-9/9W/3000K	1241.8 lm	9 W	70	
115-1723		LED-9/9W/4000K	1172.8 lm	9 W	80	
115-1723-70		LED-9/9W/4000K	1310.8 lm	9 W	70	
115-1724		LED-9/18W/2700K	1862.7 lm	18 W	80	
115-1724-70		LED-9/18W/2700K	2000.7 lm	18 W	70	
115-1725		LED-9/18W/3000K	2000.7 lm	18 W	80	
115-1725-70		LED-9/18W/3000K	2276.7 lm	18 W	70	
115-1726		LED-9/18W/4000K	2138.7 lm	18 W	80	
115-1726-70		LED-9/18W/4000K	2414.6 lm	18 W	70	
115-1727		LED-9/27W/2700K	2828.6 lm	27 W	80	
115-1727-70		LED-9/27W/2700K	3242.5 lm	27 W	70	
115-1728		LED-9/27W/3000K	2966.6 lm	27 W	80	
115-1728-70		LED-9/27W/3000K	3380.5 lm	27 W	70	

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	115-1729	LED-9/27W/4000K	3104.5 lm	27 W	80
	115-1729-70	LED-9/27W/4000K	3518.5 lm	27 W	70
