

#### Description

IP66, Class I. Class II on request. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. PMMA main lens. Integral EC electronic converter in thermally separated compartment. DALI. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Optional 2200 K version available. To be specified at time of ordering.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	<b>RAL7016</b>
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	<b>RAL9016</b>			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK09			

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter. DALI
Surge protection	6/6 kV (optional SP10)
Energy efficiency	C-D (Light source)

### Additional information

Windage	0.160 m <sup>2</sup>
Lifetime	Ta=25° L90B10 > 90000h

**Options**

**Light distribution**



[R65] rectangular, side throw



[S65] asymmetric, side throw

**Colour temperature**



2700K



3000K



4000K



**Nominal Watt**

9 W

18 W

27 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	
 <p>[R65] rectangular, side throw</p>	115-1712	LED-9/9W/2700K	1024.5 lm	9 W	80	
	115-1712-70	LED-9/9W/2700K	1095.2 lm	9 W	70	
	115-1713	LED-9/9W/3000K	1095.2 lm	9 W	80	
	115-1713-70	LED-9/9W/3000K	1271.8 lm	9 W	70	
	115-1714	LED-9/9W/4000K	1201.2 lm	9 W	80	
	115-1714-70	LED-9/9W/4000K	1342.5 lm	9 W	70	
	115-1715	LED-9/18W/2700K	1907.7 lm	18 W	80	
	115-1715-70	LED-9/18W/2700K	2049 lm	18 W	70	
	115-1716	LED-9/18W/3000K	2049 lm	18 W	80	
	115-1716-70	LED-9/18W/3000K	2331.7 lm	18 W	70	
	115-1717	LED-9/18W/4000K	2190.4 lm	18 W	80	
	115-1717-70	LED-9/18W/4000K	2473 lm	18 W	70	
	115-1718	LED-9/27W/2700K	2896.9 lm	27 W	80	
	115-1718-70	LED-9/27W/2700K	3320.9 lm	27 W	70	
	115-1719	LED-9/27W/3000K	3038.2 lm	27 W	80	
	115-1719-70	LED-9/27W/3000K	3462.2 lm	27 W	70	
	115-1720	LED-9/27W/4000K	3179.6 lm	27 W	80	
	115-1720-70	LED-9/27W/4000K	3603.5 lm	27 W	70	
	 <p>[S65] asymmetric, side throw</p>	115-1721	LED-9/9W/2700K	1000.3 lm	9 W	80
		115-1721-70	LED-9/9W/2700K	1069.3 lm	9 W	70
115-1722		LED-9/9W/3000K	1069.3 lm	9 W	80	
115-1722-70		LED-9/9W/3000K	1241.8 lm	9 W	70	
115-1723		LED-9/9W/4000K	1172.8 lm	9 W	80	
115-1723-70		LED-9/9W/4000K	1310.8 lm	9 W	70	
115-1724		LED-9/18W/2700K	1862.7 lm	18 W	80	
115-1724-70		LED-9/18W/2700K	2000.7 lm	18 W	70	
115-1725		LED-9/18W/3000K	2000.7 lm	18 W	80	
115-1725-70		LED-9/18W/3000K	2276.7 lm	18 W	70	
115-1726		LED-9/18W/4000K	2138.7 lm	18 W	80	
115-1726-70		LED-9/18W/4000K	2414.6 lm	18 W	70	
115-1727		LED-9/27W/2700K	2828.6 lm	27 W	80	
115-1727-70		LED-9/27W/2700K	3242.5 lm	27 W	70	
115-1728		LED-9/27W/3000K	2966.6 lm	27 W	80	
115-1728-70		LED-9/27W/3000K	3380.5 lm	27 W	70	

---

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
	115-1729	LED-9/27W/4000K	3104.5 lm	27 W	80
	115-1729-70	LED-9/27W/4000K	3518.5 lm	27 W	70

---