

Description

IP66, Class I. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. PMMA main lens. Silicone CCG[®] Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral electronic converter with DALI interface in thermally separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Optional 2200 K version available. To be specified at time of ordering.

Including 0.5 m cable with a cable connector.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP66			
Impact resistance	IK09			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral electronic converter with DALI interface in thermally separated compartment
Surge protection	6/6 kV (optional SP10)
Energy efficiency	C-D (Light source)

Additional information

Windage	0.160 m ²
Lifetime	Ta=25° L90B10 > 90000h

Options

Light distribution



[R65] rectangular, side throw



[S65] asymmetric, side throw

Colour temperature



2700K



3000K



4000K



Nominal Watt

9 W

18 W

27 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [R65] rectangular, side throw	115-1712	LED-9/9W/2700K	1024.5 lm	9 W	80
	115-1713	LED-9/9W/3000K	1095.2 lm	9 W	80
	115-1714	LED-9/9W/4000K	1201.2 lm	9 W	80
	115-1715	LED-9/18W/2700K	1907.7 lm	18 W	80
	115-1716	LED-9/18W/3000K	2049 lm	18 W	80
	115-1717	LED-9/18W/4000K	2190.4 lm	18 W	80
	115-1718	LED-9/27W/2700K	2896.9 lm	27 W	80
	115-1719	LED-9/27W/3000K	3038.2 lm	27 W	80
	115-1720	LED-9/27W/4000K	3179.6 lm	27 W	80
	 [S65] asymmetric, side throw	115-1721	LED-9/9W/2700K	1000.3 lm	9 W
115-1722		LED-9/9W/3000K	1069.3 lm	9 W	80
115-1723		LED-9/9W/4000K	1172.8 lm	9 W	80
115-1724		LED-9/18W/2700K	1862.7 lm	18 W	80
115-1725		LED-9/18W/3000K	2000.7 lm	18 W	80
115-1726		LED-9/18W/4000K	2138.7 lm	18 W	80
115-1727		LED-9/27W/2700K	2828.6 lm	27 W	80
115-1728		LED-9/27W/3000K	2966.6 lm	27 W	80
115-1729		LED-9/27W/4000K	3104.5 lm	27 W	80