



#### Description

IP66, Class I. Class II on request. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. PMMA main lens. The luminaire is factory sealed and does not need to be opened during installation. Integral EC converter. Factory installed LED circuit board. Removable LED boards for upgrading. CAD-optimised indirect optics for superior illumination and glare control.

## Specifications

### Material description

Colours	<b>RAL9004</b>	<b>RAL9006</b>	<b>RAL9007</b>	<b>RAL7016</b>
	Signal black	White aluminium	Grey aluminium	Anthracite grey
	<b>RAL9016</b>			
	Traffic white			
Ingress protection	IP66			
Impact resistance	IK08			

### Electrical description

Power supply	220-240V / 50-60 Hz
Surge protection	6/6 kV (optional SP10)
Energy efficiency	C-D (Light source)

### Additional information

Windage	0.190 m <sup>2</sup>
Lifetime	Ta=25° L70B50 > 50000h

**Options**

Light distribution	Colour temperature	Nominal Watt
 [C50]	 2700K	24 W 37 W
 [C60]	 3000K	
 [R50]	 4000K	

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C50]	115-1730	LED-1/24W/2700K	3089.2 lm	24 W	80
	115-1731	LED-1/24W/3000K	3218.9 lm	24 W	80
	115-1732	LED-1/24W/4000K	3356.2 lm	24 W	80
	115-1733	LED-1/37W/2700K	4687.2 lm	37 W	80
	115-1734	LED-1/37W/3000K	4828.3 lm	37 W	80
	115-1735	LED-1/37W/4000K	5106.7 lm	37 W	80
 [C60]	115-1736	LED-1/24W/2700K	2780.3 lm	24 W	80
	115-1737	LED-1/24W/3000K	2897 lm	24 W	80
	115-1738	LED-1/24W/4000K	3020.6 lm	24 W	80
	115-1739	LED-1/37W/2700K	4218.5 lm	37 W	80
	115-1740	LED-1/37W/3000K	4345.5 lm	37 W	80
	115-1741	LED-1/37W/4000K	4596.1 lm	37 W	80
 [R50]	115-1893	LED-1/24W/2700K	3101.3 lm	24 W	80
	115-1891	LED-1/24W/3000K	3231.5 lm	24 W	80
	115-1892	LED-1/24W/4000K	3369.4 lm	24 W	80
	115-1896	LED-1/37W/2700K	4705.6 lm	37 W	80
	115-1894	LED-1/37W/3000K	4847.3 lm	37 W	80
	115-1895	LED-1/37W/4000K	5126.8 lm	37 W	80