



Description

IP66, Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. PMMA main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral electronic converter with DALI interface in thermally separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Optional 2200 K version available. To be specified at time of ordering.

Including 0.5 m cable with a cable connector.

Specifications

Material description

Colours	RAL9004 Signal black	RAL9007 Grey aluminium	RAL7016 Anthracite grey	RAL9016 Traffic white
Ingress protection	IP66			
Impact resistance	IK08			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral electronic converter with DALI interface in thermally separated compartment
Surge protection	6/6 kV (optional SP10)
Energy efficiency	C-D (Light source)

Additional information

Windage	0.190 m ²
Lifetime	Ta=25° L90B10 > 90000h

Options

Light distribution



[R65]



[S65] asymmetric, side throw

Colour temperature



2700K



3000K



4000K

Nominal Watt

36 W

54 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [R65]	115-1742	LED-18/36W/2700K	3851.5 lm	36 W	80
	115-1743	LED-18/36W/3000K	4136.8 lm	36 W	80
	115-1744	LED-18/36W/4000K	4422.1 lm	36 W	80
	115-1745	LED-18/54W/2700K	5848.5 lm	54 W	80
	115-1746	LED-18/54W/3000K	6133.8 lm	54 W	80
	115-1747	LED-18/54W/4000K	6419.1 lm	54 W	80
	 [S65] asymmetric, side throw	115-1748	LED-18/36W/2700K	3651.5 lm	36 W
115-1749		LED-18/36W/3000K	3921.9 lm	36 W	80
115-1750		LED-18/36W/4000K	4192.4 lm	36 W	80
115-1751		LED-18/54W/2700K	5544.8 lm	54 W	80
115-1752		LED-18/54W/3000K	5815.3 lm	54 W	80
115-1753		LED-18/54W/4000K	6085.8 lm	54 W	80