

#### Description

IP66, Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. PMMA main lens. Integral EC electronic converter in thermally separated compartment. DALI. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Optional 2200 K version available. To be specified at time of ordering

## Specifications

### Material description

Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9007</b> Grey aluminium
Fasteners	PCS Polymer Coated Stainless Steel Hardware		
Ingress protection	IP66		
Impact resistance	IK08		
Corrosion resistance	5CE+Primer		

### Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter. DALI
Surge protection	In-pole surge protection SP10 device supplied. Please refer to WE-EF installation instructions for details. Use suffix +A for Integral surge protection.
Energy efficiency	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.

### Additional information

Windage	0.205 m <sup>2</sup>
Lifetime	Ta=40° L90B10 > 90000h

**Options**

**Light distribution**



[R65] rectangular, side throw



[S65] asymmetric, side throw

**Colour temperature**



2700K



3000K





4000K

**Nominal Watt**

36 W

54 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [R65] rectangular, side throw	115-1766	LED-18/36W/2700K	4058.7 lm	36 W	80
	115-1767	LED-18/36W/3000K	4359.3 lm	36 W	80
	115-1768	LED-18/36W/4000K	4660 lm	36 W	80
	115-1769	LED-18/54W/2700K	6163.2 lm	54 W	80
	115-1770	LED-18/54W/3000K	6463.9 lm	54 W	80
	115-1771	LED-18/54W/4000K	6764.5 lm	54 W	80
 [S65] asymmetric, side throw	115-1772	LED-18/36W/2700K	3821.6 lm	36 W	80
	115-1773	LED-18/36W/3000K	4104.7 lm	36 W	80
	115-1774	LED-18/36W/4000K	4387.7 lm	36 W	80
	115-1775	LED-18/54W/2700K	5803.1 lm	54 W	80
	115-1776	LED-18/54W/3000K	6086.2 lm	54 W	80
	115-1777	LED-18/54W/4000K	6369.3 lm	54 W	80