

Description

IP66, Class I. Class II on request. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Integral EC electronic converter in thermally-separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Pre-wired post complete with cable connecting box and fuse for mains connection.

Optional Eco Step Dim® Motion version available. To be specified at time of ordering.

Supplied as a complete luminaire (luminaire head and standpipe). Please note: The standpipe height must be entered for the photometric calculation.

Specifications

Material description

Body	Marine-grade, all-aluminium construction			
Lens	Polycarbonate lens			
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9016 Traffic white	RAL7016 Anthracite grey
	RAL9007 Grey aluminium			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10)
Energy efficiency	D-E (Light source)

Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

Options

Light distribution



[C60] symmetric distribution

Colour temperature



3000K



4000K




2700K

Nominal Watt

17 W

12 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C60] symmetric distribution	117-0320	LED-1/12W/2700K	710.6 lm	12 W	80
	117-0223	LED-1/12W/3000K	758.7 lm	12 W	80
	117-0224	LED-1/12W/4000K	799.4 lm	12 W	80
	117-0321	LED-1/17W/2700K	1086.2 lm	17 W	80
	117-0201	LED-1/17W/3000K	1136.2 lm	17 W	80
	117-0202	LED-1/17W/4000K	1184.3 lm	17 W	80