

### Description

IP66. Class I. IK10. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. CAD-optimized indirect optics for superior illumination and glare control. Integral driver in thermally separated compartment. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Pre-wired post complete with cable connecting box and fuse for mains connection.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Specifications

### Material description

Body	Marine-grade, all-aluminium construction			
Lens	Polycarbonate lens			
Colors	<b>RAL9004</b>	<b>RAL9016</b>	<b>RAL8019</b>	<b>RAL9007</b>
	Signal black	Traffic white	Grey brown	Grey aluminium
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			

### Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	Integral 10kV Surge Protector
Energy efficiency	D-E (Light source)

### Additional information




Height (inches)	23.62
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L70B50 > 50000h

**Options**

**Light distribution**    **Color temperature**    **Nominal Watt**




[C60]

	3000K
	4000K
	2700K

17 W  
12 W

### Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[C60]</p>	117-0320	LED-1/12W/2700K	710.6 lm	12 W	80
	117-0321	LED-1/17W/2700K	1086.2 lm	17 W	80
	117-0201	LED-1/17W/3000K	1136.2 lm	17 W	80
	117-0201	LED-1/17W/3000K	1136.2 lm	17 W	80
	117-0202	LED-1/17W/4000K	1184.3 lm	17 W	80
	117-0202	LED-1/17W/4000K	1184.3 lm	17 W	80