

Description

IP66, Class I. Class II on request. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG[®] Controlled Compression Gasket. Polycarbonate main lens. Integral EC electronic converter in thermally-separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Pre-wired post complete with cable connecting box and fuse for mains connection.

Optional Eco Step Dim[®] Motion version available. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade, all-aluminium construction			
Lens	Polycarbonate lens			
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9016 Traffic white	RAL7016 Anthracite grey
	RAL9007 Grey aluminium			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			





Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10)
Energy efficiency	D-E (Light source)


Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

Options

Light distribution	Colour temperature	Nominal Watt
 [C60]	 3000K	17 W
	 4000K	12 W
	 2700K	

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C60]	117-0322	LED-1/12W/2700K	710.6 lm	12 W	80
	117-0225	LED-1/12W/3000K	758.7 lm	12 W	80
	117-0227	LED-1/12W/4000K	799.4 lm	12 W	80
	117-0323	LED-1/17W/2700K	1086.2 lm	17 W	80
	117-0199	LED-1/17W/3000K	1136.2 lm	17 W	80
	117-0200	LED-1/17W/4000K	1184.3 lm	17 W	80