

Description

IP66, Class I. Class II on request. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Integral EC electronic converter in thermally-separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Pre-wired post complete with cable connecting box and fuse for mains connection.

Optional Eco Step Dim® Motion version available. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade all-aluminium construction			
Colours	RAL9004 Signal black	RAL9006 White aluminium	RAL9016 Traffic white	RAL7016 Anthracite grey
	RAL9007 Grey aluminium			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10)
Energy efficiency	D-E (Light source)

Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

Options

Light distribution




[C60] symmetric distribution

Colour temperature



3000K



4000K




2700K

Nominal Watt

24 W

17 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C60] symmetric distribution	117-0324	LED-1/17W/2700K	724.9 lm	17 W	80
	117-0207	LED-1/17W/3000K	758.2 lm	17 W	80
	117-0208	LED-1/17W/4000K	790.4 lm	17 W	80
	117-0325	LED-1/24W/2700K	1000.3 lm	24 W	80
	117-0209	LED-1/24W/3000K	1042.3 lm	24 W	80
	117-0210	LED-1/24W/4000K	1086.7 lm	24 W	80