

### Description

IP66, Class I. Class II on request. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Integral EC electronic converter in thermally-separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Pre-wired post complete with cable connecting box and fuse for mains connection.

Optional Eco Step Dim® Motion version available. To be specified at time of ordering.

## Specifications

### Material description

Body	Marine-grade all-aluminium construction			
Colours	<b>RAL9004</b> Signal black	<b>RAL9006</b> White aluminium	<b>RAL9016</b> Traffic white	<b>RAL7016</b> Anthracite grey
	<b>RAL9007</b> Grey aluminium			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			

### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10)
Energy efficiency	D-E (Light source)

### Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

**Options**

**Light distribution**



[C60] symmetric distribution

**Colour temperature**



3000K



4000K




2700K

**Nominal Watt**

24 W

17 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C60] symmetric distribution	117-0324	LED-1/17W/2700K	724.9 lm	17 W	80
	117-0207	LED-1/17W/3000K	758.2 lm	17 W	80
	117-0208	LED-1/17W/4000K	790.4 lm	17 W	80
	117-0325	LED-1/24W/2700K	1000.3 lm	24 W	80
	117-0209	LED-1/24W/3000K	1042.3 lm	24 W	80
	117-0210	LED-1/24W/4000K	1086.7 lm	24 W	80