

Description

IP66. Class I. IK10. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. CAD-optimized indirect optics for superior illumination and glare control. Integral driver in thermally separated compartment. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Pre-wired post complete with cable connecting box and fuse for mains connection.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Body	Marine-grade all-aluminium construction			
Colors	RAL9004 Signal black	RAL9016 Traffic white	RAL8019 Grey brown	RAL9007 Grey aluminium
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE			

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	Integral 10kV Surge Protector
Energy efficiency	D-E (Light source)

Additional information




Height (inches)	23.62
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
Lifetime	Ta=25°/40° L70B50 > 50000h

Options

Light distribution **Color temperature** **Nominal Watt**




[C60]

	3000K
	4000K
	2700K

24 W
17 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 [C60]	117-0324	LED-1/17W/2700K	724.9 lm	17 W	80
	117-0207	LED-1/17W/3000K	758.2 lm	17 W	80
	117-0207	LED-1/17W/3000K	758.2 lm	17 W	80
	117-0208	LED-1/17W/4000K	790.4 lm	17 W	80
	117-0208	LED-1/17W/4000K	790.4 lm	17 W	80
	117-0325	LED-1/24W/2700K	1000.3 lm	24 W	80
	117-0209	LED-1/24W/3000K	1042.3 lm	24 W	80
	117-0209	LED-1/24W/3000K	1042.3 lm	24 W	80
	117-0210	LED-1/24W/4000K	1086.7 lm	24 W	80
	117-0210	LED-1/24W/4000K	1086.7 lm	24 W	80