

Description

IP66, Class I. Class II on request. IK10. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Integral EC electronic converter in thermally-separated compartment. CAD-optimised indirect optics for superior illumination and glare control. Factory installed LED circuit board. Pre-wired post complete with cable connecting box and fuse for mains connection.

Optional Eco Step Dim® Motion version available. To be specified at time of ordering.

Specifications

Material description

Body	Marine-grade all-aluminium construction								
Colours	<table><tr><td>RAL9004 Signal black</td><td>RAL9006 White aluminium</td><td>RAL9016 Traffic white</td><td>RAL7016 Anthracite grey</td></tr><tr><td>RAL9007 Grey aluminium</td><td></td><td></td><td></td></tr></table>	RAL9004 Signal black	RAL9006 White aluminium	RAL9016 Traffic white	RAL7016 Anthracite grey	RAL9007 Grey aluminium			
RAL9004 Signal black	RAL9006 White aluminium	RAL9016 Traffic white	RAL7016 Anthracite grey						
RAL9007 Grey aluminium									
Fasteners	PCS Polymer Coated Stainless Steel Hardware								
Ingress protection	IP66								
Impact resistance	IK10								
Corrosion resistance	5CE								

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Standard. Optional DALI version available. To be specified at time of ordering.
Surge protection	10/10kV (SP10)
Energy efficiency	D-E (Light source)

Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

Options

Light distribution



[C60] symmetric distribution

Colour temperature



4000K



3000K




2700K

Nominal Watt

17 W

24 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI
 [C60] symmetric distribution	117-0326	LED-1/17W/2700K	724.9 lm	17 W	80
	117-0203	LED-1/17W/3000K	758.2 lm	17 W	80
	117-0204	LED-1/17W/4000K	790.4 lm	17 W	80
	117-0327	LED-1/24W/2700K	1000.3 lm	24 W	80
	117-0205	LED-1/24W/3000K	1042.3 lm	24 W	80
	117-0206	LED-1/24W/4000K	1086.7 lm	24 W	80