

Description

Impact-Rated Bollard. IP66. Class I. IK10. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. CAD-optimized indirect optics for superior illumination and glare control. Integral driver in thermally separated compartment. Factory-installed LED circuit board.

Crash rated for small vehicles travelling up to 40mph (SC40), pick-up vehicles travelling up to 40mph (PU40), and medium-duty vehicles travelling up to 30mph (M30).

Pre-wired post complete with cable connecting box and fuse for mains connection.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Specifications

Material description

Colors	RAL9004 Signal black	RAL9007 Grey aluminium	RAL9016 Traffic white	RAL8019 Grey brown
Gasket	Silicone CCG® Controlled Compression Gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware			
Ingress protection	IP66			
Impact resistance	IK10			

Electrical description

Additional information

Lifetime	Ta=25°/40° L70B50 > 90000h
----------	----------------------------

Options

Light distribution



[C60] symmetric distribution

Color temperature



3000K




4000K

Nominal Watt

17 W

24 W

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI
 <p>[C60] symmetric distribution</p>	114-6906	LED-1/17W/3000K	758.2 lm	17 W	80
	114-6907	LED-1/17W/3000K	758.2 lm	17 W	80
	114-6908	LED-1/17W/3000K	758.2 lm	17 W	80
	114-6905	LED-1/17W/3000K	758.2 lm	17 W	80
	114-6910	LED-1/17W/4000K	790.4 lm	17 W	80
	114-6912	LED-1/17W/4000K	790.4 lm	17 W	80
	114-6911	LED-1/17W/4000K	790.4 lm	17 W	80
	114-6909	LED-1/17W/4000K	790.4 lm	17 W	80
	114-6914	LED-1/24W/3000K	1042.3 lm	24 W	80
	114-6915	LED-1/24W/3000K	1042.3 lm	24 W	80
	114-6916	LED-1/24W/3000K	1042.3 lm	24 W	80
	114-6913	LED-1/24W/3000K	1042.3 lm	24 W	80
	114-6918	LED-1/24W/4000K	1086.7 lm	24 W	80
	114-6919	LED-1/24W/4000K	1086.7 lm	24 W	80
	114-6920	LED-1/24W/4000K	1086.7 lm	24 W	80
	114-6917	LED-1/24W/4000K	1086.7 lm	24 W	80