




Description

Tubular steel, constant section, hot dipped galvanised. 5CE+Primer superior corrosion protection, including PCS hardware. Powdercoat finish in black RAL 9004, grey aluminium RAL 9007, anthracite grey RAL 7016 or white RAL 9016. Surface mounting flange plate with die-cast aluminium cover to conceal mounting hardware. Service door.

Spigot dimensions may vary, dependent on type of luminaire used, and must be specified at time of ordering.

Planted root is available depending on site-specific requirements; to be ordered separately.



Part ID	D1	B	C	H1	A	T1	Weight (kg)
270-9333	114	244	365	2500	20	70×400	41
270-9334	114	244	365	3000	20	70×400	45
270-9335	114	244	365	3500	20	70×400	50
270-9336	114	244	365	4000	20	70×400	58
270-9337	114	244	365	4500	20	70×400	61
270-9338	114	244	365	5000	20	70×400	66
270-9339	114	244	365	5500	20	70×400	70
270-9283	140	244	365	2500	20	90×400	57.5
270-9284	140	244	365	3000	20	90×400	65.5
270-9285	140	244	365	3500	20	90×400	72.5
270-9286	140	244	365	4000	20	90×400	87
270-9287	140	244	365	4500	20	90×400	94.5
270-9288	140	244	365	5000	20	90×400	102
270-9289	140	244	365	5500	20	90×400	111.5